



- Third generation Microdialysis Analyzer for point-of-care and advanced research
- Monitoring up to eight patients
- Batch analysis capacity of 16 samples

Monitoring of tissue Metabolic Markers

MICRODIALYSIS ANALYZER

ISCUS^{flex} is the third generation Microdialysis Analyzer for point-of-care monitoring and advanced research. The analyzer uses enzymatic reagents and colorimetric measurements to monitor tissue chemistry from virtually any tissue or organ in the body.

Microdialysis is a monitoring technique for continuous sampling of tissues and organs. Chemical substances in the interstitial fluid are sampled by a microdialysis catheter and analyzed in ISCUS^{flex}.

ISCUS^{flex} offers unique opportunities to optimize patient treatment in the ICU by detecting pathological changes before clinical signs become evident. M Dialysis offers catheters for monitoring the brain, liver, abdomen, muscle, adipose tissue and skin.

Enhanced Features and Optimized Performance

ISCUS^{flex} combines reliability and flexibility. This analyzer offers the opportunity to monitor up to eight patients at a time and is ideal for use in the intensive care. With a capacity of 16 vials, ISCUS^{flex} offers batch analysis for advanced clinical and research. The throughput of the analyzer is maximum 30 measurements per hour.

The analyzer is easy to operate by medical professionals as well as researchers. Up to six different reagents and automated control samples provide unique opportunities for early detection of metabolic crisis, ischemia and to guide post-operative interventions. Data is displayed as trendcurves for easy and fast interpretation.

Available Reagents: Glucose Lactate Pyruvate Glycerol Glutamate Urea







Key Features of the ISCUS^{flex}:

- $\mathsf{ISCUS}^{\mathsf{flex}}$ offers unique opportunities to individualize and optimize patient care in the ICU by detecting pathological changes before clinical signs become evident
- Continuous and near real-time monitoring of metabolites sampled by M Dialysis's suite of Microdialyis catheters
- High flexibility with the possibility to monitor up to eight patients simultaneously, with 16 sample positions
- Quick one-button analysis in less than two minutes per analyte with six available reagents: glucose, lactate, pyruvate, glycerol, glutamate and urea
- Automatic flushing of sample after analysis, automatic calibration and quality control
- Removable vial cassette with 16 positions for batch analysis. ISCUS^{flex} is capable of running low concentration samples for research purposes
- A new and improved graphic user interface makes it easy to operate
- ISCUS^{flex} is delivered with the ICUpilotTM software that enables you to visualize, compare and compute patient data on a separate computer
- Maximum throughput is 30 measurements per hour

Technical information

Dimensions	430 (H) x 350 (W) x 270 (D) mm	Warm-up time	10 minutes
Weight	29 lbs/13 kg	Measuring time	30 seconds
Voltage	100-240 V~, 50/60 Hz	Throughput time/test	90 seconds
Power consumption	100 VA	Detector type	Single beam filter photometer
Type of protection	Class 1, Type B	Light source	Class1LED
Measurement principle	Kinetic enzymatic analyzer	Wavelengths	375 and 530 nm
Vials	Microvials or CMA Glass vials	Detector cell	Capillary flow cell 10 mm, 2 µL
Samples	Microdialysates	Detector cell	Temperature 99 °F/37 °C
Min. sample volume	Sum of sample volumes per analyte + 2 μL	Assay imprecision	<4 % rel. standard deviation within run for "Control Samples Normal"
Pipetting imprecision	<2 $\%$ (at 0.5 $\mu L) rel. standard deviation$	External Communications Ports	SD Card Slot USB Port Network Port
Calibration	Automatic (every 6 hrs)		

Ordering information

5				
ISCUS ^{flex} Microdialysis Analyzer, for Clinical Use	8003295			
ISCUS ^{flex} Microdialysis Analyzer, for Research Use Only				
Accessories:				
Reagent Set A: Glucose 1x6mL, Lactate 1x6mL, Pyruvate 1x6mL, Glycerol 1x6mL, Calibrator A 1x6mL				
Reagent Set B: Glucose 1x6mL, Lactate 1x6mL, Pyruvate 1x6mL, Glycerol 1x6mL, Glutamate 1x4mL, Calibrator A1x6mL				
Reagent Set C: Glucose 1x6mL, Lactate 1x6mL, Pyruvate 1x6mL, Calibrator A 1x6mL				
	Ref.No.		Ref.No.	
Glucose Reagent, 5/pkg	P000023	Control Samples, 3 levels, 3x3/pkg	8010201	
Lactate Reagent, 5/pkg	P000024	Rinsing fluid, 0.5 L, 8/pkg	8002171	
Pyruvate Reagent, 5/pkg	P000063	Waste bottle, 0.5 L, 8/pkg	8002161	
Glycerol Reagent, 5/pkg	P000025	Thermal print paper, 30.5 m, 4/pkg	8002162	
Glutamate Reagent, 5/pkg	P000064	Sample Cannula, 1/pkg	8001721	
Urea Reagent, 5/pkg	P000026	Vial Cassette, 1/pkg	8003409	
Calibrator A, 10/pkg	P000057	Secure Digital Memory Card, 1/pkg	8002360	
CE marked according to the European Directive for In Vitro D				

M Dialysis AB Hammarby Fabriksväg 43, SE-120 30 Stockholm, Sweden Tel: +46-8-47010 20 Fax: +46-8-47010 55 www.mdialysis.com US Office: 73 Princeton Street, North Chelmsford, MA 01863 USA Tel: (866)868-9236 (978) 251-1940 Fax: (978) 251-1960 E-mail: usa@mdialysis.com